

Material No.	Part No.	Tyre Size	(Meas. Rim. WD) APPD. Rim WD.	O.D. "	Sect. Width "	Tread Width "	Circ. "	Compound	Suggested Tube	Approx. WT. LBS
90000024651	3551	26X10.50-15LT	(8.0) 7.0-9.0	26.3	10.4	8.7	83	M5	90000000289	20
90000024643	3554	28X11.50-15LT	(8.0) 8.0-10.0	28.2	11.1	8.8	89	M5	90000000289	2224
90000031239	3561	28X12.50-15LT	(10.0) 9.0-11.0	28.0	12.6	10.1	88	M5	90000000290	34
90000024645	3556	31X16.50-15LT	(12.0) 11.0-14.0	31.9	16.0	13.4	100	M5	90000000291	35
90000024646	3557	32X17.50-15LT	(14.0) 12.0-15.0	32.2	17.9	14.4	101	M5	90000000291	39
90000024647	3560	34X18.50-16LT	(16.0) 16.0-16.0	34.4	18.5	13.8	108	X5	90000000291	27
90000028490	3574	28X11.50-17LT	(9.0) 8.5-10.5	28.5	11.1	9.5	90	M5	-	

- All Bias ET, Street R tyres must be matched to be ½" roll out.
- Warning: Do not use on dyno!
- Caution: It is not recommended that radial and non-radial tyres be mixed on the same vehicle.
- Highlighted yellow row indicates new sizes.